

CRUXMOTO

2018 – 2019 Honda Accord Air Release Headlight Overlays

Thank you for purchasing our Precut Head light overlays. These instructions will guide you through the process of installing these overlays on your vehicle. If for any reason you need some help please contact us: Sales@cruxmoto.com FB.com/cruxmotorsports

Install Time: 10 mins

It is recommended that you apply these graphics in a warm space over 50 degrees Fahrenheit

What else you will need: Squeegee, Microfiber Towel, Rubbing Alcohol, Heat Gun

For our installation video of this process please visit:

www.youtube.com/user/CruxMotorsports and search Honda Accord Head Light.

1. Clean the light thoroughly with rubbing alcohol and microfiber towel. Make sure light is completely clean and dry before applying decal, this will ensure for a smooth dirt free application.
2. Once the light is clean, peel the decal from the backing paper. Make sure your finger tips are also clean, the material will pick the dirt off your fingers and stick to the adhesive if so.
3. Align film starting towards the back of the car and work your way forward. You will want to leave a little overhang of film over the gap between the headlight and the fender.
4. Once main portion of the overlay is applied you will want to focus on the gap area.
5. Using a heat gun on a low setting apply a little heat to the overlay in a smooth pass over the film.
6. Use your thumb to start to roll the film into the gap.
7. Lastly, reapply heat and use a bondo card or squeegee to work the film into the rest of the gap.